

TECHNICAL SPECIFICATIONS: 4000 SERIES DISTRIBUTING VALVE

SPECIFICATIONS

- *Constructed of High Strength, Non-Corrosive ABS Polymer*
- *Flow Range: **4 Outlet Valve:** 10-40 GPM
6 Outlet Valve: 10-25 GPM*
- *Pressure Rating: 25 - 75 PSI*
- *Pressure Loss: **4 Outlet Valve***

Flow (GPM)	10	20	30	40
PSI Loss	2.0	3.0	4.5	6.4

6 Outlet Valve

Flow (GPM)	10	20	30
PSI Loss	2.5	4.5	7.5
- *Inlet: Slip and Glue Connection to 1 1/4" PVC Pipe*
- *Outlets: Slip and Glue Connections*
4 Outlet Valve
To 1 1/4" PVC Pipe

6 Outlet Valve
To 1" PVC Pipe
- *Dimensions: Height 5 3/4"
Width 5 3/4"*

MODELS

4 Outlet Models

4402 - Cammed for 2 Zone Operation
4403 - Cammed for 3 Zone Operation
4404 - Cammed for 4 Zone Operation

6 Outlet Models

4602 - Cammed for 2 Zone Operation
4603 - Cammed for 3 Zone Operation
4604 - Cammed for 4 Zone Operation
4605 - Cammed for 5 Zone Operation
4606 - Cammed for 6 Zone Operation

HOW TO SPECIFY



K-Rain offers a complete line of irrigation equipment, designed, engineered and manufactured in the USA.

- Single Station Controllers
- Short Duration Controllers
- Distributing Valves Up To 6 Zones
- Pump Start Relays
- Gear Driven Sprinklers
- Spray Heads

K RAIN

IDEAS IN IRRIGATION

K-Rain Manufacturing Corp.
1640 Australian Avenue
Riviera Beach, FL 33404 USA
PH: 561 844-1002
FAX: 561 842-9493
EMAIL: krain@k-rain.com
WEB: <http://www.k-rain.com>