



3/4" - 261S Series - Part/Full Circle - Brass Impact Sprinklers

[Home](#)

[Search](#)

Catalog

- Brass Valves
- Quick Coupler Valves
- Impact Sprinklers
- RainCoach™
- Sprinkler Accessories
- Rotary Sprinklers
- Nozzles and Adapters
- Accessories
- Warranty

Help

Contact Us

Catalog	Performance Charts	Repair Parts	Printer friendly
----------------	------------------------------------	------------------------------	----------------------------------



261SA



261SD

Designed for large turf areas, dust control, nurseries and general purpose use.

261S Series

Features and Benefits:

- Solid brass construction.
- Anti-backsplash drive arm.
- 20° to 340° arc or full circle.
- Stainless steel drive spring.
- "Sure Seal®" sand load bearing assembly.
- Chemical resistant bearing seals.
- Stainless steel trip assembly & collars.
- Adjustable diffuser pin all models.
- Adjustable deflector plate(261SD and 261DST models only).
- Double nozzle or single nozzle and plug.

Specifications

- 3/4" Male inlet, National Pipe thread (NPT).
- Optional, British Standard Thread (BS).
- Solid brass nozzle.
- Nozzle thread top drive 1/4" NPT.
- Lower nozzle 3/8" NPT.

Operating Ranges:

	U.S.	Metric
Pressure:	30 - 60 psi	2.07 - 4.48 bars
Flow:	3.94 - 13.73	14.94 - 52.02 l/min
Spacing:	41 - 50 feet	12.50 - 15.24 m
Trajectory:	25°	

To Specify:

261SA	10	
Model	Nozzle Code	Options

NOZZLE CODE		
Code	Inches	mm
06	3/32"	2.40
08	1/8"	3.20
10	5/32"	4.0
11	11/64"	4.4
12	3/16"	4.8
13	13/64"	5.2
14	7/32"	5.6
PG	Plug	

MODEL DESCRIPTIONS	
Model No	Description
261SA	Sure Seal® Adjustable diffuser pin
261SD	Sure Seal® Adjustable deflector plate & diffuser pin
261SAT	Sure Seal® bearing, diffuser pin, anti-splash arm
261SDT	Sure Seal® bearing, deflector plate, diffuser pin & anti-backsplash arm
261SATLC	Sure Seal® bearing, diffuser pin, anti-backsplash arm & locking collars
OPTION	For BSPT inlet, add (BS) to model number



261SAT



261SDT



261SATLC