



# 1" - 360/380 Series - Part/Full Circle - Brass Impact Sprinklers

[Home](#)

[Search](#)

<a href="#">Catalog</a>	<a href="#">Performance Charts</a>	<a href="#">Repair Parts</a>	<a href="#">Printer friendly</a>
-------------------------	------------------------------------	------------------------------	----------------------------------

**Catalog**

- Brass Valves
- Quick Coupler Valves
- Impact Sprinklers
- RainCoach™
- Sprinkler Accessories
- Rotary Sprinklers
- Nozzles and Adapters
- Accessories
- Warranty

**Help**

**Contact Us**

*Well suited for large landscape irrigation requirements, pastures, logging, mining, and waste water treatment.*



360SA



380SA

**360S & 380S Series**

**Features and Benefits:**

- Solid brass construction.
- Stainless steel drive spring.
- "Sure Seal®" sand load bearing assembly.
- 20° to 340° arc or full circle operation.
- Double nozzle or single nozzle and plug configuration.
- Chemical resistant bearing seals.
- Cast brass trip assembly.
- Stainless steel trip collars.
- Adjustable diffuser pin.

**Specifications**

- 1" male inlet, (NPT) on 360SA.
- 1" female inlet (NPT) on 380SA.
- Optional, British Standard Thread (BS).
- Solid brass nozzle.

**Operating Ranges:**

	U.S.	Metric
Pressure:	35 - 80 psi	2.41 - 5.52 bar
Flow:	7.75 - 44.01 gpm	29.36 - 166.58 l/min
Spacing:	49 - 77 feet	14.94 - 23.47 m
Trajectory:	23°	

*To Specify:*

360SA	18 / 08	
Model	Nozzle Code	Options

NOZZLE CODE		
Code	Inches	mm
08	1/8"	3.20
14	7/32"	5.6
16	1/4"	6.4
18	9/32"	7.1
20	5/16"	7.9
22	11/32"	8.7
24	3/8"	9.5
PG	Plug	

MODEL DESCRIPTIONS	
Model No	Description
360SA	Adjustable diffuser pin, male bearing
380SA	Adjustable diffuser pin, female bearing
OPTION	For BSPT inlet, add (BS) to model number