



1/2" Wedge Drive - Full Circle - Brass Impact Sprinklers

[Home](#)

[Search](#)

[Catalog](#)

[Performance Charts](#)

[Printer friendly](#)

Catalog

- Brass Valves
- Quick Coupler Valves
- Impact Sprinklers
- RainCoach™
- Sprinkler Accessories
- Rotary Sprinklers
- Nozzles and Adapters
- Accessories
- Warranty

Help

Contact Us



15SW-23

The model 15SW impact sprinkler is designed for agricultural use in orchards, solid sets, hand lines, crop cooling and frost control.

15SW & 411W23 Series
1/2" Full Circle Impact Sprinkler - Wedge Drive

Features and Benefits:

- Solid brass construction.
- Stainless steel drive spring.
- Plastic, self-cleaning wedge drive assembly.
- "Sure Seal®" sand load bearing assembly.
- Bearing assembly hood for longer wear life.
- Chemical resistant bearing seals.
- 23° angle of trajectory.
- Fine thread or standard nozzles.
- 1/2" male inlet, National Pipe thread (NPT).
- Optional, British Standard Thread (BS).
- Solid brass nozzle.
- 15SW nozzle thread, 3/8 - 24 UNF.
- Optional 411W23 series nozzle thread, 3/8 - 28 UN.
- Fine thread nozzles use part # 41125-XX.

Operating Ranges:

	U.S.	Metric
Pressure:	30 - 65 psi	2.07 - 4.48 bars
Flow:	.64 - 2.88 gpm	2.42 - 10.9 l/min
Spacing:	25 - 41 feet	7.62 - 12.50 m
Trajectory:	23°	

Specifications:

- 1/2" Male inlet, National Pipe Thread (NPT).
- Solid brass nozzle.
- 15S nozzle thread, 3/8" - 24 UNF.
- Optional 41000 series nozzle thread, 3/8" - 28 UN.

MODEL DESCRIPTIONS	
Model No	1/2" Full Circle, Brass Impact Sprinklers
15SW23	23° angle
411W23	23° angle, fine thread nozzle body
OPTION	For BSPT outlet, add (BS) to model number

To Specify:

	NOZZLE CODE
--	-------------

15SW	23	06		<i>Code</i>	<i>Inches</i>	<i>mm</i>
Model	Trajectory	Nozzle Code	Options	04	1/16"	1.60
				05	5/64"	2.00
				06	3/32"	2.40
				07	7/64"	2.80